

DIVISION III**DIVISION III: MODIFIED.****QUALIFYING TRACTORS:****1959 AND OLDER****WEIGHT CLASSES:****3100, 3600, 4100, 4600, 5100, 5600, 6100, 6600, 7100,
7600, 8100, 8600, 9600, 10600, 11600****1) GENERAL RULES:****SEE GENERAL RULES THAT APPLY TO ALL TRACTORS.****2) AGE:****DRIVERS MUST BE AT LEAST 16 YEARS OLD. DRIVERS 16, 17 OR 18 YEARS OF AGE MUST HAVE VALID DRIVERS' LICENSES OR LEARNERS' PERMITS AND WRITTEN PARENTAL/GUARDIAN PERMISSION.****3) SAFETY:****ALL TRACTORS MUST HAVE A WORKING SAFETY KILL SWITCH.****4) DRAWBAR:****DRAWBARS MUST NOT EXCEED 20 INCHES IN HEIGHT OR BE LESS THAN 18 INCHES FROM CENTER OF AXLE TO HOOKING POINT. NO PART OF DRAW BAR MAY EXTEND REARWARD BEYOND POINT OF HOOK. DRAWBARS MUST BE STATIONARY IN ALL DIRECTIONS. NO CLEVISES.****5) WEIGHTS:****WEIGHTS MUST NOT EXTEND PAST REAR TIRES AND CANNOT BE MORE THAN 11 FEET FROM THE CENTER OF THE REAR AXLE TO THE FURTHEST POINT FORWARD.****6) TIRES AND RIMS:****MAXIMUM TIRE SIZE - 18.4 x 38. ANY RIM WIDTH. NO RADIAL TIRES. NO STEEL WHEELS. TWO-WHEEL DRIVE ONLY. NO DUAL WHEELS. ANY CUT ALLOWED ON TIRES.**

7) RPM:

RPMS ALLOWED WILL BE DETERMINED BY THE NATPA RPM CHART ANY TRACTOR NOT LISTED WILL USE MANUFACTURER'S DATA. A 10% MARGIN OF ERROR WILL BE PERMITTED. ALL TRACTORS TO HAVE POSITIVE THROTTLE STOPS WITH A WORKING GOVERNOR IN THE STOCK LOCATION.

8) SPEED:

NOT TO EXCEED 8 MPH. NO SHIFTING OF TAs. THE MARKER FOR DIVISION III SPEED WILL ALSO BE USED AS THE MARK TO STOP THE TRACTOR IF DRIVER WISHES TO RESTART PULL.

9) TRACTORS MANUFACTURED TO USE DIESEL FUEL ONLY CANNOT BE CONVERTED TO GAS OR LP. TRACTORS MUST BE NATURALLY ASPIRATED. NO TURBOS OR BLOWERS - EXCEPT OLIVER 99 GM, ETC.

10) TRACTORS MUST HAVE THE STOCK ENGINE, FRAMES, TRANSMISSION, REAR END, AND AXLE HOUSINGS OR MANUFACTURER'S REPLACEMENT. STOCK HEADS AND THEIR REPLACEMENTS ARE TO REMAIN UNCHANGED IN OUTSIDE APPEARANCE. NO 7-BOLT MAIN BLOCKS IN OLIVERS; NO 12-PORT HEADS; NO 99-HEADS; NO 1600 SERIES HEADS. AC WC/WD/WD-45 CAN USE D-17 ENGINE. IH H, 350, M, 450 & JD A/B/G CAN USE POWER BLOCKS. NO M/M-800 HEADS OR BLOCKS. DUAL EXHAUST AND HEADERS ARE ALLOWED.

11) ENHANCED ELECTRICAL SYSTEMS PERMITTED IN ALL CLASSES. NO REV LIMITERS ALLOWED.

12) REPLACEMENT CARBURETORS WITH NO MODIFICATION OF CARBURETOR. OVERHAND OF CARBURETOR TO MANIFOLD IS NOT ALLOWED.

13) NO INCREASED HEIGHT IN ANY TRACTORS (I.E.: DECK PLATES, SHIMS, GIRDLES) EXCEPT FOR STOCK GASKET.

14) OLIVER 66, FARMALL H, AC WC, FORD 800 AND ABOVE AND LIKE-SIZE TRACTORS ARE NOT ALLOWED IN CLASSES BELOW 3600#. MASSEY 33, OLIVER 77, JD A 1939 AND DOWN AND LIKE-SIZE TRACTORS ARE NOT ALLOWED IN CLASSES BELOW 4100#. OLIVER 88, FARMALL M, MASSEY 44, MM U, JD G, CASE C/O, JD A 1940 AND UP AND LIKE-SIZE TRACTORS ARE NOT ALLOWED IN CLASSES BELOW 4600#. MASSEY 55, IH W-9, IH WK040, CASE LA, CASE 600, MOLINE GB, MOLINE GBD, OLIVER 99 AND ALL LIKE-SIZE TRACTORS ARE NOT ALLOWED BELOW 5600#.