

DIVISION II

DIVISION II: SEMI-MODIFIED, COMPETITIVE PULLERS WITH NEAR STOCK TRACTORS, PISTON KITS, ETC.

QUALIFYING TRACTORS:

1959 AND OLDER OR PRODUCTION MODELS THAT STARTED IN 1959.

WEIGHT CLASSES:

3100, 3600, 4100, 4600, 5100, 5600, 6100, 6600, 7100, 7600, 8100, 8600, 9600, 10600, 11600.

1) GENERAL RULES:

SEE GENERAL RULES THAT APPLY TO ALL TRACTORS.

2) ENTRY:

A DIVISION II TRACTOR MAY ALSO PULL IN DIVISION III IF THE TRACTOR MEETS THE RULES FOR DIVISION III. DIVISION II TRACTORS CANNOT DROP TO DIVISION I.

3) MAXIMUM TIRE SIZE:

0-4600# 170 SQ. IN. MAX., 4601 - 6600# 229 SQ. IN. MAX., 6601 - 8600# 300 SQ. IN. MAX. SEE TIRE SIZE CHART BELOW FROM FIRESTONE TRACTION FIELD AND ROAD AND FIRESTONE FIELD AND ROAD CHARTS. MAXIMUM TIRE SIZE OF 38".

4) RIMS AND WHEELS:

TIRES MUST BE TIRE MANUFACTURER'S RECOMMENDED RIM WIDTH. PRESSED STEEL WHEELS ARE ALLOWED FRONT AND REAR. NO CHROME OR ALUMINUM WHEELS ALLOWED. SHAVED TIRES ARE ALLOWED, CUT FROM THE BACK ONLY. NO TIRES CUT FROM THE FRONT SIDE.

5) SPEED:

UP TO SECOND GEAR (NOT TO EXCEED 2ND). NOT ALLOWED TO SHIFT TORQUE, ALL TORQUES MUST BE IN "DIRECT" OR HIGH SIDE. TRACTORS EQUIPPED WITH HI-LO RANGE TRANSMISSIONS MUST PULL IN LOW RANGE. EXAMPLE: 444 MASSEY, 400 CASE.

6) WEIGHTS:

SUITCASE WEIGHTS AND CUSTOM-MADE WEIGHT BRACKETS ARE PERMITTED. FRONT WEIGHT BRACKET AND WEIGHTS SHOULD EXTEND NO FURTHER THAN 11 FEET FROM CENTER OF REAR AXLE. WEIGHTS MAY NOT EXTEND PAST REAR TIRES.

7) ENGINE:

STOCK BLOCK, NATURALLY ASPIRATED. EXCEPTIONS OLIVER 99 GM, ETC. STOCK HEAD, MANIFOLD, AND CARBURETOR (BY PART NUMBER). IF AN EXTERNAL PART IS NOT IN THE PARTS BOOK OR REPLACEMENT PARTS BOOK FOR THAT SPECIFIC TRACTOR IT CANNOT BE USED. EXCEPTION: STRAIGHT EXHAUST PIPE ALLOWED, AIR FILTER MUST BE USED ALTHOUGH IT MAY BE OF ANY TYPE. RPM - 110% OF FACTORY HIGH IDLE SPECIFICATION (RPM USED IS THE LATEST MODEL RPM FOR THAT MAKE OF TRACTOR). NO ELECTRONIC IGNITIONS (EXCEPTION: AN ELECTRONIC PICKUP INSIDE THE ORIGINAL STOCK DISTRIBUTOR OR MAGNETO CAN BE USED, BUT DISTRIBUTOR OR MAGNETO MUST MAINTAIN ORIGINAL APPEARANCE). NO SQUARE COILS, MSD COILS OR CHROME COILS ALLOWED. HEADERS AND DUAL EXHAUST ARE NOT ALLOWED. POWER BLOCKS ARE NOT ALLOWED.

8) HITCHES:

MINIMUM 18" BACK FROM THE CENTER OF THE REAR AXLE AND A MAXIMUM OF 18" DRAWBAR HEIGHT. HITCH MATERIAL CANNOT BE THINNER THAN 3/4" AND NOT THICKER THAN 1.25". HITCH HAS TO HAVE A 3" HOLE WITH 1" MATERIAL THICKNESS AROUND THE HOLE OR A STRAIGHT CLEVIS BOLTED OR PINNED TIGHTLY TO THE DRAWBAR WITH A MINIMUM OF 2.5" HOLE. TOP OF HITCH ADJUSTER CANNOT BE ABOVE CENTERLINE OF AXLE OR HUB. HITCHES AND DRAWBARS MUST BE STATIONARY IN ALL DIRECTIONS. HITCH MUST BE EASILY ACCESSIBLE (SLED OPERATORS DISCRETION).

9) APPEARANCE:

TRACTORS MUST MAINTAIN ORIGINAL STOCK APPEARANCE. IF A PART IS NOT FOUND IN THE MANUFACTURERS PARTS BOOK IT CANNOT BE USED. NO EXTRA ACCESSORIES ALLOWED WITH THE EXCEPTION OF WEIGHT BRACKETS, HANG-ON WEIGHTS, WHEELIE BARS, WHEELS, RIMS, BOLT-ON HUBS, DRAWBAR, MUFFLER AND AIR CLEANER. BATTERY BOXES MAY BE MOVED FROM STOCK MOUNTING LOCATION. NO ALUMINUM ALLOWED EXCEPT FOR WEIGHT BRACKETS AND WHEELIE BARS. NO CHROME ALLOWED EXCEPT FOR EXHAUST PIPES. HOMEMADE SIDE-SHIELDS ARE NOT ALLOWED. EXCEPTION: FACTORY SIDE-SHIELDS ON OLIVER TRACTORS AND THE LIKE. NO HOMEMADE REAR-END COVERS ALLOWED. ALL GUARDS, SHROUDS, COVERS, AND SHIELDS SHALL BE IN PLACE AS FROM THE FACTORY AND BE MADE OF ORIGINAL MATERIAL (STEEL OR IRON) AND AS NEAR LIKE FACTORY AS POSSIBLE. SEAT MUST BE AN ORIGINAL SEAT OR A MANUFACTURED SEAT MADE FOR A FARM TRACTOR PLACED WITH STOCK MOUNTINGS (SUCH AS TSC). ALTERNATORS AND STRAIGHT PIPES ARE ALLOWED.

10) SPONSORS:

ADVERTISING PLAQUES MAY BE PUT ON TRACTOR AS LONG AS IT DOES NOT INTERFERE WITH THE TECH COMMITTEE'S CHECKING OF TRACTOR.

DIVISION II

0 - 4600# CLASS 170 SQ. IN.**13.6 X 38 - 168 SQ. IN.****14.9 X 28 - 170 SQ. IN.****4601 - 6600# CLASS 229 SQ. IN.****14.9 X 38 - 200 SQ. IN.****15.5 X 38 - 189 SQ. IN.****16.9 X 34 - 229 SQ. IN.****6601 - 8600# CLASS 300 SQ. IN.****18.4 X 38 - 300 SQ. IN.****16.9 X 38 - 252 SQ. IN.****18.4 X 28 - 250 SQ. IN.**

TATPA ADOPTED NATPA RULES IN 1999. REVISIONS MADE FOR TATPA IN APRIL 2002 AND NOVEMBER 2003. HCAT&EC ADOPTED TATPA RULES IN 2006. REVISIONS MADE FOR HCAT&EC IN JUNE 2006.