

DIVISION I: ORIGINAL STOCK TRACTORS ONLY.**QUALIFYING TRACTORS:**

1959 AND OLDER OR PRODUCTION MODELS THAT STARTED IN 1959.

WEIGHT CLASSES:

**3100, 3600, 4100, 4600, 5100, 5600, 6100, 6600, 7100, 7600,
8100, 8600, 9600, 9600, 10600, 11600.**

1) GENERAL RULES:

SEE GENERAL RULES THAT APPLY TO ALL TRACTORS.

2) ENTRY:

A TRACTOR CANNOT BE ENTERED IN CLASSES BELOW ITS MANUFACTURED SHIPPING WEIGHT. A DIVISION I TRACTOR MAY ALSO PULL IN DIVISION II IF THE TRACTOR MEETS THE RULES FOR DIVISION II. DIVISION II TRACTORS CANNOT DROP TO DIVISION I.

3) MAXIMUM TIRE SIZE:

0 - 3600# 130 SQ. IN. MAX., 3601-4600# 145 SQ. IN. MAX., 4601-5600# 170 SQ. IN. MAX., 5601-6600# 229 SQ. IN. MAX., 6601-7600# 284 SQ. IN. MAX., 7601-8600# 300 SQ. IN. MAX. NO CUT OR SHAVED TIRES. SEE TIRE SIZE CHART BELOW FROM FIRESTONE TRACTION FIELD AND ROAD AND FIRESTONE FIELD AND ROAD CHARTS.

4) RIMS AND WHEELS:

TRACTORS MUST HAVE OEM RECOMMENDED DIAMETER RIMS AND OEM WHEELS. TIRES MUST BE TIRE MANUFACTURERS RECOMMENDED RIM WIDTH. WHEELS WITH RIMS FOR MANUFACTURERS ORIGINAL RECOMMENDATIONS TO INCLUDE CUT-DOWNS FOR TRACTORS THAT MAY HAVE ORIGINALLY BEEN ON STEEL WHEELS.

5) SPEED:

LOW GEAR ONLY (1ST GEAR). NOT ALLOWED TO SHIFT TORQUE, ALL TORQUES MUST BE IN "DIRECT" OR HIGH SIDE. TRACTORS EQUIPPED WITH HI-LO RANGE TRANSMISSIONS MUST PULL IN LOW RANGE. EXAMPLE 444 MASSEY, 400 CASE.

5) SPEED:

LOW GEAR ONLY (1ST GEAR). NOT ALLOWED TO SHIFT TORQUE, ALL TORQUES MUST BE IN "DIRECT" OR HIGH SIDE. TRACTORS EQUIPPED WITH HI-LO RANGE TRANSMISSIONS MUST PULL IN LOW RANGE. EXAMPLE 444 MASSEY, 400 CASE.

6) WEIGHTS:

WEIGHTS OF BOLT-ON TYPE TO EITHER THE FRONT OR THE BACK WHEELS. WEIGHTS CAN BE MADE. THEY MUST BE ROUND, MADE OF METAL AND CLOSELY RESEMBLE ORIGINAL MANUFACTURED WEIGHTS. NO CONCRETE OR SUITCASE WEIGHTS ALLOWED. WHEEL WEIGHTS MUST BE ATTACHED TO THE WHEELS.

7) ENGINE:

STOCK BLOCK, NATURALLY ASPIRATED. EXCEPTIONS: OLIVER 99 GM, ETC. STOCK HEAD, MANIFOLD, AND CARBURETOR (BY PAN NUMBER). MANIFOLDS ARE TO BE REPLACEMENT - MANUFACTURED PARTS ACCEPTED FOR THAT MAKE AND MODEL OF TRACTOR. STOCK RPM ENGINE PARTS NOT IN PARTS BOOK OR REPLACEMENT PARTS BOOK FOR THAT SPECIFIC TRACTOR CANNOT BE USED. EXCEPTIONS: DISTRIBUTORS CAN BE USED ON ANTIQUE TRACTORS. A FACTORY COIL MUST BE USED. NO ELECTRONIC IGNITIONS, SQUARE COILS, MSD COILS OR CHROME COILS ALLOWED.

8) HITCHES:

MAXIMUM 16" HEIGHT (STATIONARY IN ALL DIRECTIONS) LOCKED AT 16" ON TRACTORS SUCH AS IH FAST HITCH, FORD 3-POINT HITCH, ETC. HITCHES MUST BE FACTORY, UNALTERED FOR THAT SPECIFIC TRACTOR. OPERATOR MUST FURNISH A STRAIGHT UP AND DOWN CLEVIS WITH A MINIMUM OPENING OF 2.5" BOLTED OR PINNED TIGHTLY WITH SPACERS TO THE DRAW BAR. HITCH MEASURED AT HOOK POINT OF CLEVIS. FARMALL H'S AND M'S MUST PULL FROM AN ORIGINAL DRAWBAR HOOKED TO THE ORIGINAL BELLY HOOK POINT.

9) SAFETY:

THE FRONT WHEELS OF THE TRACTOR ARE NOT ALLOWED TO EXCEED 16" OFF THE GROUND DURING A PULL. OPERATOR IS TO PROVIDE A LINKED CHAIN OR DEVICE ATTACHED PARALLEL TO THE CENTER OF THE FRONT AXLE, A MAXIMUM OF 16" ON THE GROUND. CHAIN MUST BE DRAGGING AT THE TIME TRACTOR IS HOOKED. WHEELIE BARS ARE OPTIONAL. IF WHEELIE BARS MEETING UPPER DIVISION REQUIREMENTS ARE USED, THE ABOVE NOSE HEIGHT RULE DOES NOT APPLY. A MINIMUM OF 5' SLED HITCH CHAIN MUST BE USED.

10) APPEARANCE:

TRACTORS MUST MAINTAIN ORIGINAL STOCK APPEARANCE. IF A PART IS NOT FOUND IN THE MANUFACTURER'S PARTS BOOK IT CANNOT BE USED. NO EXTRA ACCESSORIES ALLOWED. NO ALUMINUM OR CHROME ALLOWED EXCEPT FOR EXHAUST PIPES. ALL GUARDS, SHROUDS, COVERS AND SHIELDS SHALL BE IN PLACE AS FROM FACTORY AND BE MADE OF ORIGINAL MATERIAL (STEEL OR IRON) AND AS NEAR FACTORY AS POSSIBLE. NO HOMEMADE REAR END COVERS ALLOWED. SEAT MUST BE AN ORIGINAL SEAT OR A MANUFACTURED SEAT MADE FOR A FARM TRACTOR PLACED WITH A STOCK MOUNTINGS (SUCH AS TSC). HOME MADE SIDE-SHIELDS WILL NOT BE ALLOWED. EXCEPTION: FACTORY SIDE SHIELDS ON OLIVER TRACTORS AND THE LIKE. ALTERNATORS AND STRAIGHT PIPES ARE ALLOWED.

11) SPONSORS:

ADVERTISING PLAQUES OR SIGNS MAY BE PUT ON TRACTOR AS LONG AS IT DOES NOT INTERFERE WITH THE TECH COMMITTEE'S CHECKING OF TRACTOR.

0 - 3600# CLASS 130 SQ.IN.

11.2 x 38 - 120 SQ. IN.
 11.2 x 36 - 115 SQ. IN.
 12.4 x 28 - 126 SQ. IN.
 13.6 x 24 - 130 SQ. IN.

3601 - 4600# CLASS 145 SQ.IN.

12.4 x 38 - 140 SQ. IN.
 12.4 x 36 - 135 SQ. IN.
 13.6 x 28 - 145 SQ. IN.
 14.9 x 26 - 144 SQ. IN.

4601 - 5600# CLASS 170 SQ. IN.

13.6 x 38 - 168 SQ. IN.
 14.9 x 28 - 170 SQ. IN.

5601 - 6600# CLASS 229 SQ. IN.

14.9 x 38 - 100 SQ. IN.
 15.5 x 38 - 189 SQ. IN.
 16.9 x 34 - 229 SQ. IN.

6601 - 7600# CLASS 284 SQ. IN.

18.4 x 34 - 584 SQ. IN.
 16.9 x 38 - 252 SQ. IN.
 18.4 x 28 - 250 SQ. IN.

7601 - 86# CLASS 300 SQ. IN.

18.4 x 38 - 300 SQ. IN.